

Product Memo

COOPER PowerTools



Cleco® D Series Pulse Tools

Cooper Power Tools is pleased to introduce our latest addition to the D Series pulse tool family, the 120PTHD554 and 110PTHD55Q. These new tools have 15% more torque output, 30% lower weight and more than twice the speed. The torque range is 75 – 120 Nm (110 NM for quick change). The new models incorporate best-in-class setup, adjustment and maintenance. Features include patented three-chambered air motor, torque adjustment at the back of the tool, relocated torque signal port and reduced trigger pull.

Cleco D Series Specifications

COOPER PowerTools

| Model Number | Drive Type | Torque Range | | Free Speed | Weight | | Working CFM | Recommended Hose Size |
|---|-------------|--------------|--------|------------|--------|------|-------------|-----------------------|
| | | Ft. -Lbs. | Nm | RPM | lbs. | kg | | |
| Pistol Grip – Shut-off Models – Trigger Throttle | | | | | | | | |
| 11PTHD65Q | 1/4" QC | 4.4-8.1 | 6-11 | 6500 | 1.87 | 0.85 | 12.3 | 3/8" |
| 11PTHD652 | 1/4" Sq.Dr. | 4.4-8.1 | 6-11 | 6500 | 1.81 | 0.82 | 12.3 | 3/8" |
| 11PTHD653 | 3/8" Sq.Dr. | 4.4-8.1 | 6-11 | 6500 | 1.83 | 0.83 | 12.3 | 3/8" |
| 20PTHD75Q | 1/4" QC | 7.3-14.7 | 10-20 | 7500 | 1.92 | 0.87 | 12.3 | 3/8" |
| 20PTHD753 | 3/8" Sq.Dr. | 7.3-14.7 | 10-20 | 7500 | 1.90 | 0.86 | 12.3 | 3/8" |
| 35PTHD65Q | 1/4" QC | 14.7-25.8 | 20-35 | 6500 | 2.2 | 1.0 | 16 | 3/8" |
| 35PTHD653 | 3/8" Sq.Dr. | 14.7-25.8 | 20-35 | 6500 | 2.2 | 1.0 | 16 | 3/8" |
| 55PTHD603 | 3/8" Sq.Dr. | 22.1-40.5 | 30-55 | 6000 | 2.4 | 1.1 | 19 | 3/8" |
| 80PTHD60Q | 7/16" QC | 36.9-59 | 50-80 | 6000 | 3.2 | 1.45 | 19 | 3/8" |
| 80PTHD604 | 1/2" Sq.Dr. | 36.9-59 | 50-80 | 6000 | 3.1 | 1.4 | 19 | 3/8" |
| 110PTHD55Q | 7/16" QC | 55.3-81.1 | 75-110 | 5500 | 3.75 | 1.7 | 30 | 1/2" |
| 120PTHD554 | 1/2" Sq.Dr. | 55.3-88.5 | 75-120 | 5500 | 3.75 | 1.7 | 30 | 1/2" |

General:
Tools rated at 6.0 bar (87 PSI)
Tools rated at < 80 dBA

Standard Equipment:
Suspension bail; torque adjustment screwdriver; Torque error proofing signal port.

Our new D Series Family now covers torques ranging from 6 NM to 120 NM. All D Series pulse tools are in stock and ready for shipment.

This memo, PM772 is available in the Memos section and the price list ASM-1B is available in the Price Lists section of the Distributor Sign-In website.

For more information on our wide product offering, please visit our website at www.cooperpowertools.com. If you do not have web access, please contact our Customer Service at 1-800-845-5629 with your requirements and shipping information. Cooper Power Tools is always committed to offering the best tool solutions for increased productivity.